

High-precision Solid and Liquid Densimeter



BK-DMH120D



BK-DMH300D

Application:

It is suitable for the field of quality management, cost control, new materials researching, scientific academies, researching key laboratories, quality inspection, etc.

Any form of solid could be measured, including objects of hygroscopicity, non-absorbency, high-viscosity.

Measurement of special liquid such as volatile liquid, corrosivity liquid, strong acid and strong alkali liquid need optional accessory DE-20B anti corrosive liquid measuring assembly.

Features:

- * Automatically check whether density is qualified or not and prompt alarm.
- * Automatic zero tracking, buzzer warning, and overload warning.
- * Function of solution compensation: necessary if liquid other than water is used as a medium for measuring.
- * RS-232C is included.


Accessories for Densimeter

Standard Accessory:



DE-20A standard liquid measuring assembly

Optional Accessories:



DE-20B anti corrosive liquid measuring assembly



DE-40 printer

Technical Parameters:

Model		BK-DMH120D	BK-DMH300D
Capacity		0.001~120g	0.005~300g
Density Resolution		0.0001g/cm³	0.001g/cm³
Density Range		0.0001~99.9999g/cm³	0.001~99.999g/cm³
Measuring Time		About 5s	
Solid Mode	Measuring Principle	Archimedes principle	
	Measurable Items	Density of general non-absorbency solid. Density of porosity materials. Oil length of oil bearing. Porosity of porosity materials. DIN volume abrasion loss of rubber. Powder density. Water absorption rate.	
	Specific Gravity	Unibody injection forming professional specific gravity measurement frame Size: 135*50*116mm (L*W*H)	
	Measuring Frame Measuring Tank	Unibody injection forming transparent professional measuring tank Size: 169*98*83mm (L*W*H)	
	Mixed Material Percentage	Function introduction	Automatically read the percentage of the main material in composite which consist of two materials
		Setting	Freely set the density value of main material and subordinate material
		Display	Density value, percentage of main material
Liquid Mode	Measuring Principle	Archimedes principle displacement method	
	Weight Value Data Storage	3 groups	
	Specific Gravity Measuring Frame	Stainless steel specific gravity measuring frame	
	Result Display	Density and Baume value	
	Result Testing Method	Distilled water testing	
Calibration Mode		Auto correction, auto detection.	
Standard Accessories		Common Use: Tweezer, thermometer, 100G weight, windshield, power transformer. Solid Use: Tank, testing board, a set of particle measuring assembly, a set of floating body measuring assembly. Liquid Use: Measuring plate, measuring frame, DE-20A standard liquid measuring assembly	
Optional Accessories		DE-40 printer, DE-20B anti corrosive liquid measuring assembly	
Power Supply		AC110/220V±10%, 50/60Hz	
Package Size(W*D*H)mm		450*200*360	
Gross Weight(kg)		6.5	

000 «Диаэм»

Москва
ул. Магаданская, д. 7, к. 3 ■ тел./факс: (495) 745-0508 ■ sales@dia-m.ru

www.dia-m.ru

С.-Петербург
+7 (812) 372-6040
spb@dia-m.ru

Новосибирск
+7 (383) 328-0048
nsk@dia-m.ru

Воронеж
+7 (473) 232-4412
vrn@dia-m.ru

Йошкар-Ола
+7 (927) 880-3676
nba@dia-m.ru

Красноярск
+7 (923) 303-0152
krsk@dia-m.ru

Казань
+7 (843) 210-2080
kazan@dia-m.ru

Ростов-на-Дону
+7 (863) 303-5500
rnd@dia-m.ru

Екатеринбург
+7 (912) 658-7606
ekb@dia-m.ru

Кемерово
+7 (923) 158-6753
kemeroovo@dia-m.ru

Самара
+7 (915) 482-4897
samara@dia-m.ru

